

AMENDMENTS TO THE CLAIMS:

Please amend the claims to read as follows:

1. (Currently amended) A jewelry article for an interchangeable setting, comprising:
a body defining a mounting area, the mounting area holding the setting except substantially along one axis when at least a portion of the setting is positioned in the area; and
a module discrete from the setting, said module slidably coupling on the body from a direction other than along the one axis and holding the setting in the mounting area substantially along the one axis.
2. (Original) The jewelry article of claim 1, wherein the module has at least one portion positioning at least partially adjacent the setting to prevent the setting from escaping the mounting area along the one axis.
3. (Original) The jewelry article of claim 2, wherein the at least one portion of the module includes an arm inserting into a bore in the setting.
4. (Original) The jewelry article of claim 1, wherein the module has at least two portions positioning at least partially adjacent at least two portions of the setting to prevent the setting from escaping the mounting area substantially along the one axis when the setting is positioned in the area.
5. (Original) The jewelry article of claim 4, wherein the at least two portions of the module include sides of the module positioning at least partially adjacent the at least two portions of the setting in the mounting area.

6. (Currently amended) A jewelry article worn by a wearer, comprising:
an interchangeable setting;
a body defining a mounting area, the mounting area holding the setting on the body
except substantially along one axis when at least a portion of the setting is
positioned in the area; and
a module discrete from the setting, said module slidably ~~mechanically~~ coupling on the
body from a direction other than along the one axis and preventing removal of the
setting from the mounting area substantially along the one axis.
7. (Original) The jewelry article of claim 6, wherein the body has first and second sides and
wherein the mounting area is defined through the body from the first side to the second side.
8. (Original) The jewelry article of claim 7, wherein portions of the body forming the
mounting area to hold the setting are positioned along the two axes substantially orthogonal to
the one axis.
9. (Original) The jewelry article of claim 8, wherein the mounting area is at least partially
open along one of the substantially orthogonal axes to the one axis.
10. (Original) The jewelry article of claim 9, wherein the mounting area is defined by a
radius and has a circumferential dimension at least greater than half of a circle.
11. (Original) The jewelry article of claim 10, wherein the at least a portion of setting
includes a portion of a sphere, disk, or cylinder.
12. (Original) The jewelry article of claim 6, wherein the body defines a recessed portion
coupling with a portion of the module.

13. (Original) The jewelry article of claim 12, wherein the recessed portion of the body includes a bridge of the body positioned between the mounting area and an opening for wearing the article, and wherein the portion of the module fits onto the bridge from the opening for wearing the article.
14. (Original) The jewelry article of claim 6, wherein the module defines a slot coupling with a portion of the body.
15. (Original) The jewelry article of claim 14, wherein the portion of the body includes a bridge of the body positioned between the mounting area and an opening for wearing the article, and wherein the slot of the module fits onto the bridge from the opening for wearing the article.
16. (Original) The jewelry article of claim 6, wherein the module is removable from the body such that the module is interchangeable.
17. (Original) The jewelry article of claim 6, wherein the module is fixedly and movably coupled to the body.
18. (Original) The jewelry article of claim 17, further comprising a biasing member biasing the module to capture the interchangeable setting.
19. (Original) The jewelry article of claim 6, wherein the module magnetically couples to the body by one or more magnets in addition to mechanically coupling to the body.
20. (Original) The jewelry article of claim 6, wherein the module has at least one portion positioning at least partially adjacent the setting to prevent removal of the setting from the mounting area substantially along the one axis.

21. (Original) The jewelry article of claim 20, wherein the at least one portion of the module includes an arm inserting into a bore in the setting.
22. (Original) The jewelry article of claim 6, wherein the module has at least two portions positioning at least partially adjacent at least two portions of the setting to prevent removal of the setting from the mounting area substantially along the one axis.
23. (Original) The jewelry article of claim 22, wherein the at least two portions of the module include sides of the module positioning at least partially adjacent the at least two portions of the setting in the mounting area.
24. (Original) The jewelry article of claim 6, wherein the module remains mechanically coupled on the body by the wearer when the jewelry article is worn.
25. (Currently amended) A jewelry article for a wearer, comprising:
an interchangeable setting;
means for holding the setting except substantially along one axis;
means discrete from the setting for preventing removal of the setting substantially along the one axis; and
means for ~~mechanically~~ slidably coupling together the means for holding the setting and the means for preventing removal of the setting such that the interchangeable setting is substantially captured on the jewelry article, wherein said slidable coupling comprises sliding movement in a direction other than along the one axis.
26. (Currently amended) The jewelry article of claim 25, wherein the means for ~~mechanically~~ slidably coupling includes means for interchangeably fitting a first portion of the preventing means onto a second portion of the holding means.

27. (Currently amended) The jewelry article of claim 25, wherein the means for ~~mechanically~~ slidably coupling includes means for fixedly and movably coupling the holding means to the preventing means.
28. (Currently amended) The jewelry article of claim 26, wherein the means for fixedly and movably coupling further includes means for biasing the preventing means into engagement with the holding means.
29. (Currently amended) The jewelry article of claim 25, wherein the means for ~~mechanically~~ slidably coupling further includes means for magnetically coupling the holding means to the preventing means.
30. (Original) The jewelry article of claim 25, further comprising means for maintaining the preventing means and the holding means mechanically coupled together by the wearer when the jewelry article is worn.
